



picture similar

Application areas:

- Anchor injection, Ground stabilization, Rock injection
- Drill injection
- Floor level injection
- Geothermal applications
- Cavity filling
- Micro tunnelling

Mixing of:

- Cement slurries
- Anchor grout
- Bentonite slurries
- Filling material for peripheral sealing
- Insulation slurries
- Fly-ash slurries

Technical Data / Performance Data*

Mixing capacity (with 20 batches/h)	1,5	m ³ /h
Effective volume mixer	75	l
Mixing water minimum	30	l
Mixer filling level (bag loading)	870	mm
Solids grain size	max. 2	mm
Dosage liquid	1 1/4"	ball valve, manually
Level indicator (rough)	30 – 75	l; filling bar adjustable
Dosage solids	manually	bag loading grid
Mixer outlet	Storz C	2" standard coupling DIN 14307, alternatively 2" IG
Water connection	Storz C	1 1/4" standard coupling DIN 14307, max.6 bar; or Geka-claw coupling
Cleaning connection	DN 20	Geka-claw coupling
Power connection	CEE-plug	16 A, 5-pole with phase inverter
Power input	2,2	KW
Voltage	400	V; 50 Hz
Dimensions	0,8 x 0,8 x 1,5	m (L x W x H)
Weight	approx.160	kg

)*The specified performance data are non-binding values that differ significantly depending on dosing, mixing and discharge times.

Description:

The batch mixer CM-75-E (manual operation) is an especially for construction site use developed compact slurry mixer for processing of bagged goods. It is particularly suitable for mixing bentonite - and cement slurries, diaphragm wall compounds or other solids-containing suspensions.

Characteristics:

- Processing of bagged goods
- Easy operation, maintenance and cleaning
- Mixer drive from above, no additional seals required
- Minimum installation and commissioning effort
- Optimal mixing quality (colloidal mixer)
- Low space required
- Easy operation (crane, lift truck, forklift)
- Little operating costs

Features:

- ✓ **Colloidal mixer CM-75** for colloidal processing of slurries
- ✓ **Water dosage DN 32** with hand-operated ball valve
- ✓ **Level indicator (rough)** via adjustable filling bar
- ✓ **Recirculation and emptying line** (easy uncoupling) with 3-way valve
- ✓ **Base frame** galvanized, lift truck handling is possible from the long or front sides, forklift handling from the front sides, central lifting eye on the mixer motor
- ✓ **Toggle switch** for mixer motor
- ✓ **Electrical input** with motor protection switch and phase inverter

Accessories / Equipment Version (not included in delivery):

- Water meter
- Mixing scale

GERTECMaschinen- und Anlagenbau
GmbHGewerbepark 3
D-87477 SulzbergPhone.: +49(0)8376-987 91-0
Fax: +49(0)8376-987 91-99
info@gertec-gmbh.de

Art.No.: 43552

Edition: 2022-06-08

Technical specifications are
subject to change

Page 2 / 2